



H = Height, W= Width, D = Depth



## EI - central

The el-central is moist resistente, but place and fit the el-central on a dry and suitable place on board. Let the connectors point downwards. The el-central can also be flush mounted. Different front panels is available for flush mounting (Accessories).

The el-central got 1 DEFA PlugIn male inlet contact and 2 outlets. 1 PlugIn female contact for DEFA chargers etc. and 1 schuko contact for other electric accessories. All the connectors is placed on one side. The earth wire contact is connected to a "katode protected diode bridge" reducing the corrosion when conected to shore power.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

### Item number

700433 (1 x DEFA PlugIn inlet, 1 x DEFA PlugIn outlet, 1 x Schuko outlet)

Front panel (flush mounting): 701101 (White) og 701104 (Mahogany)

\* Must be ordered separately.

Delivered in single packaging.

### Installation

Equipment damage and possible injuries may result from an incomplete understanding of the installation and operation of the charger.

If you are unfamiliar with electrical systems: consult us, a dealer or a licensed electrician.

Read the mounting and user guide carefully.

### Maintenance

Check the earth-leakage circuit-breaker function within and after the season (marine/boat).

### Technical specifications

Voltage [VAC]	230
Current [A]	16
IP Rating [IP]	44
H/W/D [mm] (ex. connector)	175x120x90
Weight [kg]	0,92
Certifications	EN61558-2-4 ISO 13297