



230V ~ 50Hz  



MiniPlug Xtreme Connection cable 1,5mm²

DEFA MiniPlug Xtreme connection cable is adapted to DEFA MiniPlug inlet cable and gives a reliable and good connection from electricity outlets to the car. The MiniPlug Xtreme is more durable and is suitable for cold weather and rough treatment. Xtreme has a black cap to distinguish from the MiniPlug.

Only use original DEFA MiniPlug connection cable together with DEFA MiniPlug inlet cable and connect the DEFA MiniPlug connection cable only to an earthed power socket. Fit and install parts according to the enclosed usage & installation guide.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007.

In addition to this, our engine heaters and cables are conforming to the requirements of ISO/ TS 16949:2002.

Item no

460955 (2,5m). Weight: 309 gr. (22ex x 2,5m pr. assembly box)

460957 (5,0m). Weight: 535 gr. (12ex x 5,0m pr. assembly box)

Part of

MiniPlug Xtreme connection cable is delivered only as single product.

Use

Connect (A) to the DEFA MiniPlug inlet cable contact in the front of your vehicle. Make sure not to harm or damage the connection cable. Ensure not to damage the cable insulation by squeezing the cable under the hood or in the doorway. Keep the cap on when the cable is not in use.

Maintenance

Disconnect the cable. Apply some silicon spray on the MiniPlug contact terminals before and after the season and ensure that either the cable or cap is damaged.

Technical specifications

Voltage [V]	250
Fuse [A]	16
Length [m]	2.5, 5.0
MiniPlug (A) IP rating	IP44
Testing & acceptance	EN 50066, EN 60309-1